CARS OF



SPORTS

1933

DIMENSIONS OF S.S.I.

Overall	length o	of car	-		-	-	-	-	2	- 2	7	15' 6"
	width	**	-	-	-	÷	-	-	-	-	~	5′ 3½″
	height	,,				-	-	-	-	-	- 2	4' 7"
Width o	f body	inside	÷		÷	-	+		φ	-	-	3' 10"
**	doors					2	*		•			3' 6"
Centre o	of back	rest to pe	dals	(adjus	table)	+	-	2	÷	44"	max.,	38" min.
Height o	of back	rest (front	and	rear)	-		*	*	*		-	2' 1"
Depth of	f body	inside	-	្			2	-		÷	÷	3′ 5″
Back of	front se	eat to cent	re of	rear	seat	back	rests			42"	max.,	37" min.

DIMENSIONS OF S.S.II.

Overall	length	of car		-	*	*	*	*			*	12'	0"
22.5	width	,,		2	2		-	-		-	-	4'	6"
**	height	11	-	-	-		-	-	-	-	2	4'	6"
Width	of body	inside		-	-			-		-		3′	7"
**	doors	8 2	-	-		-		92	-	2	-	2' 10)1"
Centre	of back	rest to	pedals	(adjus	table)	-	*	-	7	48"	max.,	40" m	in.
Height	of back	rest -	-		-	2	-4					2′	1"
Depth	of body	inside	-								-	3'	5"

A DISTINCTIV

SWALLOW COACHBUILDING COMPANY LTD. SWALLOW ROAD COVENTRY

Telephone 8027 (6 lines)

Telegrams : Swallow, Coventry

COLOUR SCHEMES

ACAREFULLY selected range of artistic colour schemes is available—finished. in highly polished cellulose, Body and wheels: Nile Blue, Apple Green, Carnation Red. Buff, Birch Grey or Primrose Black head, trunk and wings. For those who desire a Coloured Head the following are available: Apple Green body and wheels, Olive Green head, trunk and wings. Carnation Red body and wheels, Lake head, trunk and wings. Buff body and wheels, Chocolate Brown head, trunk and wings.



CUSTOMERS requiring aluminium, or Bluemel's enamel numbers, should specify same with their orders, as special size plates are required.

Chromium plated domed spot lamp and horn case to match with dumb iron fixing, may be supplied at £1 10s. 0d. ACE Spare Wheel Cover, in Colour and Chromium, £3 15s. 0d. extra.

We reserve the right to amend the specification contained in this leaflet from time to time as may be considered necessary for the purpose of improvement.

CFASS

IN INTRODUCING the 1933 S.S. Cars, we do so with a feeling of extreme confidence that we are satisfying the demand which exists for cars possessing not only a distinctive individuality, but also those qualities desired by the discriminating motorist-exceptional road performance, accommodation and comfort.

The 1933 S.S.I is designed to fulfil the requirements of the most exacting owner. The grace of line and dignity of the new model embellish qualities of invaluable worth-smooth engine power through silent gears, a new chassis frame of immense strength, springing providing soft comfort, yet road holding qualities which are uncanny, luxurious arm-chair seating between the wheelbase, with the comfort of a Pullman coach, spacious luggage trunk, silent coachwork of lasting quality, superlative exterior finish.

The 1933 S.S.II, possessing many of the qualities of the S.S.I, is a car designed to meet the ideals of those who desire a small car embodying all the refinements usually associated with the most expensive models—luxurious seating for two adult and two juvenile passengers, spacious accommodation for luggage, in fact everything to fulfil the wishes of the most exacting owner.

Guarantee

od that if a customer fails to comply with this preliminary condition the Company will be a ing guarantee or upon any express or implied condition, warranty or guarantee.

Manufacturers' Guarantee

- (or a brief description of all circumstances which will facilitate a guick and satisfactory settlement.

 (d) if there has been any circespondence or in invoicts rendered, the Company's reference number should it.

 4. Delivery of all goods supplied by the Company under this guarantee will be made at the Company's Works.
- 5. The term "Agent" where used is in a complimentary sense only and those persons or firms who are styled the Company's "Agents" are not authorised to advertise, incur any debts, transact any business, or incur soy liabilities whistoever on the Company's behalf, nor are they authorised to give any guarantee or warranty on make any representations on the Company's part other than those constained in this document.

Guarantee as to Repairs and Overbauls

- The Guarantee and Conditions set forth above cover, and are applicable to, repairs executed by the Company, with the exception of repairs.
- Cars which are sent for repair will be driven by the Company's employees and/or Agents at the risk and responsibility of the owners only. Repairs of cars are undertaken only on the assumption that the owners give the Company authority to drive the vehicles on their behalf.



CHASSIS. Entirely new underslung chassis frame designed for extreme rigidity. The main members are triangulated in the centre by cross bracing. Wheel base, 9 ft. 11 in. Track, 4ft. 3 in.

GEAR BOX in unit with engine, four forward speeds, silent third gear type. Constant and third speed gears are of the double helical type. Easy gear change control, with extended selector action, encased in gear box extension cover, giving an ideal and close-to-hand change speed lever. Gear ratios: Top. 4-66; third, 6-15; second, 9-75; first, 16-1.

third, 6·15; second, 9·75; first, 16·1.

ENGINE. Standard six-cylinder 65·6 m/m bore×102 m/m stroke, 2054 c.c. Tax £16. Side valves: Exceptionally stiff crankshaft, seven bearing type, 2 in. diameter main bearing, 1½ in. diameter big end, dynamically and statically balanced. Aluminium pistons. Duralumin connecting rods. Detachable high compression aluminium cylinder head. Cooling system, thermo syphon circulation of water assisted by a rotor, driven from the same drive as the fan. Lubrication by gear type pump, supplying oil under pressure direct to main bearings of crankshaft, camshaft, and to big ends. All oil passages are drilled integral with cylinder block. A float situated in the sump indicates quantity of oil, whilst pressure is recorded by gauge on dash. Special oil purifier is fitted in addition to usual filter. Centralised chasis lubrication. Ignition by coil and battery. Clutch, single dry plate type. 20 h.p. engine, £10 extra.

ELECTRICAL EQUIPMENT. 12-volt set. Large type P170 head lamps, chromium plated complete with electrical dip and switch reflectors. Sports type wing lamps. Finger-tip steering wheel control.

PROPELLER SHAFT. Tubular type of large diameter, having two all-metal universal joints.

REAR AXLE. Spiral bevel type having four satellites in a bevel type differential. The actual casing is of the banjo type. All type differential. The parts very accessible.

FRONT AXLE. H-section beams, considerably dropped.

BRAKES. Bendix Duo Servo. Both foot and hand brakes operate on all four wheels.

STEERING. Marles-Veller cam and lever type, giving a pleasantly light steering. Turning circle, 38 feet.

SPRINGS. Generous half-elliptic springing. Front springs, 32 in.×1½ in. Rear, 41 in.×1½ in. Hartford's friction type shock absorbers fitted front and rear.

PETROL SUPPLY. By A.C. pump, from 12-gallon tank carried at the rear of the chassis. The pump is driven by the same gears as the engine oil pump; visible filter is provided.

WHEELS AND TYRES. Rudge-Whitworth, centre lock splined hub type racing wheels. 18 in. rims, fitted with Dunlop 28×5-50 tyres.



CHASSIS. Manufactured by The Standard Motor Company, Ltd., incorporating specially tuned engine to the following specification.

specification.

ENGINE. Four cylinder, 60·25 m/m bore, 88 m/m stroke, 1005 c.c. Tax £9. Side valves, Exceptionally stiffcrankshaft, two bearing type, both dynamically and statically balanced. Aluminium pistons, Duralumin connecting rods. Special cylinder head. Lubrication by gear type pump, supplying oil under pressure to main bearings of crankshaft, camshaft, and to big ends. All oil passages are drilled integral with cylinder block. A dip stick in the sump indicates quantity of oil, while pressure is recorded by gauge on dash. Ignition by coil and battery, automatic advance and retard. Clutch, single dry plate type.

ELECTRICAL EQUIPMENT. 6-volt lighting and starting set. Finger-tip control above steering wheel for dimming head lamps.

GEAR BOX. A four-speed box with remote control is fitted. This type provides silent third gear. The constant and third speed gears are of the double helical type, ensuring silence and easy gear change. Gear ratios: Top, 5·25-1. Third, 7·3-1. Second, 12·85-1. First, 20·0-1. Reverse, 20·0-1.

PROPELLER SHAFT. Tubular type of large diameter, having two all-metal Universal joints.

REAR AXLE. Spiral bevel type, with a bevel type differential. The axle casing is of the banjo type, all parts very accessible. FRONT AXLE. H-section beam, considerably dropped to allow

built car.

BRAKES. Bendix Duo Servo. Both foot and hand brakes operate on all four wheels.

STEERING. Worm and nut type, giving a pleasantly light steering. The turning circle of the "S.S.II. Sports" is excellent.

steering. The turning circle of the "S.S.II. Sports" is exceined, being 34 feet.

SPRINGS. Generous half-elliptic springing. Front, 27½ in.×
1½ in. Rear, 39 in.×1 in. Hartford's friction type shock absorbers fitted to front and rear axies.

fitted to front and rear axles.

PETROL SUPPLY. By Autovac from a 5-gallon tank carried at rear of chassis. A two-way reserve petrol tap is provided giving a reserve supply of \$\frac{1}{2}\$ gallon.

WHEELS AND TYRES. Special heavy type Dunlop Magna wheels, 18 in. rims, with 27x 4-75 tyres.

GENERAL DIMENSIONS. Wheelbase, 7 ft. 7 in. Track, 3 ft. 8 ji in. Width, 4 ft. 5 in.

RADIATOR. A special feature, designed to conform with the graceful body lines, fitted with emblem and filler cap. The ensemble is completed with chromium plated head lamps and louvred apron between the dumb irons.

HE . . .



SPORT

£325



£325

THE S.S.I.

RADIATOR. A special feature, entirely redesigned, conforming with the graceful body lines; fitted with chromium plated fluted front, futuristic emblem and filler cap under the bonnet. The ensemble is completed with chromium plated head lamp bar and louvred apron between the dumb irons. Cooling system incorporates new high efficiency impeller and special film block to prevent over-heating.

BUMPERS. Exceptionally substantial and of attractive appearance, are domed 3½ section. Those at the rear protect the spare wheel and trunk.

COACHWORK. Coachbuilt, with leather grained head and large travelling trunk; the body represents the finest example of craftsmanship. The body is constructed on the soundest lines and is of extreme strength. Everything possible has been done to ensure lasting and trouble-free quality. The frame is of prime quality selected ash throughout, reinforced by aluminium and metal brackets.

THE DOORS. Flush fitting, and exceptionally wide, ensuring ease of access; the doors are hinged on double-strength standing pillars from bottom side to cantrall by means of special self-aligning hinges, incorporating Enots' grease nipples. Spring loaded all-steel door checks are fitted to the bottom of the doors secured to the chassis frame. Entirely new type slam locks of positive action are fitted, Each door is fitted with adjustable Bedford buffers.

THE HEAD. Leather grained, with chromium dummy head joints. Chromium weather mould protecting door, and chromium bead down hinge pillar and waistline.









£210

THE S.S.II.

BUMPERS. Exceptionally substantial and of attractive appearance are domed 21 in. section. Those at the rear are of the quarter type. COACHWORK. Coachbuilt, with leather grained head and large travelling trunk, the body represents the finest example of craftsmanship.

THE DOORS. Flush fitting, and exceptionally wide, ensuring ease of access, are hinged on two chromium plated heavy barrel joint hinges. The locks are of the heavy tapered striking plate type with private lock incorporated in the off-side handle, the near-side lock is fitted with interior safety catch.

THE HEAD. Leather grained, with chromium dummy head joints. Chromium weather mould protecting door, and chromium bead down hinge pillar and waistline.

TRUNK. Leather grained with futuristic heavily chromium plated hinged security catches and key lock. Provides spacious accommodation for travelling cases.



TRUNK. Leather grained with futuristic heavily chromium plated hinged security catches and key lock. Three or four large suit cases are easily accommodated. Several sets of golf clubs may also be carried.

SLIDING ROOF. Perfectly flush fitting with very large quickly operated opening, which is semi-invisible when in the closed position.

position.

WINDOW LIGHTS. Safety glass winding windows.

WINDSCREEN. Patent type of entirely new design, with swept top rall and radiused corners; may be opened from top or bottom. The design incorporates jointless weather strip, thus eliminating screen leakage. The back light is mounted in chromium channel and may be opened to give additional ventilation.

BONNET. Stainless steel hinge and heavily louvred side panels with quick action security fasteners.

with quick action security fasteners.

SCUTTLE VENTILATORS are fitted on each side of the scuttle, ventilation being provided through the bonnet louvres. An armoured plate dash enclosed round all controls, including the pedals, prevents heat from entering the body.

WINGS. Exceptionally efficient and graceful design, with deep side valances ensuring adequate protection.

UPHOLSTERY. Finest quality Vaumol hide throughout, in a range of colours to tone with the exterior colour schemes, heavily pleated in artistic design.

CABINET WORK. The Instrument panel, door cappings and fillets are of polished figured walnut.

CARPETING. The floor is thickly carpeted in colours to harmonise with the exterior finish.

SEATS. The seats are of entirely new and exceptionally attractive design, providing spacious and comfortable accommodation for four adult passengers. The rear seats are constructed as two small arm chairs and are deeply sprung with Swallow patent spring case cushions and back rest. The arm rests are heavily padded with a special cushion rubber. Deep foot wells provide ample room for the passengers' legs. The front seats offering equal comfort to those at the rear are constructed on similar lines, except that they are not provided with arm rests. They are quickly adjustable by means of special ball bearing slide rails. The back rests hinge forward.

ENTRY AND EXIT. Exceptionally large doors provide extreme ease of access to and from the rear compartment.

HEAD ROOM. Ample head room for the tallest passenger is a feature made possible by the special dropped chassis frame.

INSTRUMENTS. The illuminated panel is mounted with electric clock, trip speedometer, ammeter, oil pressure gauge, electric petrol gauge.

ACCESSORIES. Complete suite of interior fittings in polished chromium incorporating interior mirror, roof lamp and switch, rear blind with driver's hand control, ash tray and companion set.



SLIDING ROOF. Entirely new design. Perfectly flush fitting and invisible in the closed position. Large opening, quickly

WINDOW LIGHTS. Safety glass winding windows.
WINDSCREEN. 11 in. Safety glass single panel, opening to any desired position, closing on to rubber insert, fitted Lucas duo blade electric wiper.

BONNET. Stainless steel hinge and heavily louvred side panels with quick action security fasteners.

SCUTTLE VENTILATORS are fitted on each side of the scuttle, ventilation being provided through the bonnet louvres. An armoured plate dash, enclosed round all controls, including the pedals, prevents heat from entering the body.

WINGS. Deeply domed 8 in. section, with swaged centres. Deep side valances ensuring adequate protection.

UPHOLSTERY. Finest quality "Vaumol" furniture hide, heavily pleated in artistic design, and thickly carpeted floor in colours to harmonise with the exterior finish.

CABINET WORK. The instrument panel, door cappings, and fillets are finished with centre panels of highly polished "Fiddle Back" Sycamore, in colours to tone with the upholstery, the moulded edges being polished black in relief.

INSTRUMENTS. The illuminated panel is mounted with clock, trip speedometer, ammeter, oil pressure gauge.

SEATS. The front seat with deeply sprung 9 in. cushion and back squab—the latter adjustable—provides maximum comfort for two, or occasionally three, adult passengers. The rear seats are designed for juvenile passengers, although suitable for the occasional use of an adult.

HEAD ROOM. Ample head room for the tallest passenger is a feature made possible by the special dropped seat well.

ACCESSORIES. The complete suite of interior fittings in polished chromium and matt finish, incorporating interior mirror, roof lamp and switch, rear blind with driver's hand control, ash tray and companion set.