

1971 XKE CONVERTIBLE

The manners of this car are impeccable. But its instincts — to spring, sprint, maneuver — are uninhibited.

Principal Dimensions: Wheel base 96 ins. Overall Length 175-5/16 ins. Dry Weight 2,464 lbs. Fuel 16¾ gals. Oil 9 qts. Water 16 qts.

Body: 2-door, all-steel. Twin bucket reclining seats with adustable headrests, upholstered in ventilated leather over foam rubber. Folding top, with large rear window, mounted on special frame to permit easy raising or lowering. Fits under rear deck. 7-dial instrument panel, including tachometer. Heater and demister standard equipment.

Engine: six-cyl, in-line, develops 245 bhp at 5,500 rpm, 263 lbs-ft torque at 3,000 rpm. Displacement 4.2 litres (4,235 ccs; 258.4 cu. ins.) Bore 3.63 ins. Stroke 4.17 ins. Compression ratio 9 to 1. Hemispherical combustion chambers. Air pollution control manifold. Twin overhead camshafts.

Transmission: Four-speed, all synchromesh. Ratio 3.54 to 1. Limited slip differential. Suspension: Four-wheel independent, torsion bars front and paired coil springs rear. Brakes: 4-wheel discs with quick-change pads. Steering: Rack and pinion. Adjustable wood-rimmed steering wheel. Wheels: 15 ins. 72-wire spokes with Dunlop Aqua-Jet radial ply 185 x 15 tires. Electrical Equipment: 12-volt battery. Alternator.

Optional Equipment: Fiberglass hardtop. Power assisted steering. Radio. Chrome wire wheels. Tinted glass. Whitewall tires. Air conditioning.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



Jaguar